DATASHEET

NXS35KIT

Single Girder Crane Kit

October 1, 2026



System Component	Specification
General	
Capacity	10,000 kg
Lift Height	10.0 m
Span	Between 3 and 21 m (bridge not included)
Single Girder Hoist	
Code	ML.NXS35HIS.041.B
Hoist Type	NXS
Trolley Type	ML
Drum	S
Falls	4/1
Capacity	10,000 kg
Duty (ISO)	ISO M5 - FEM 2m
Lift Height	10.0 m
Hoisting Speed	1.2 . . . 4.8 . . . 8.0 m/min (UltraSpeed: Q $\leq$ 25%)
Cross Travel Speed	4.8 . . . 19.2 . . . 24.0 m/min (UltraSpeed: Q $\leq$ 25%)
Control Voltage	48 V
Wire Rope	Ø11 mm 2160 N/mm^2 8 $\times$ 26 Galvanized Compact IWRC Left Lay
Drum Diameter	Ø400 mm
Drum Material	E355 / 1.0580
Hook	NR5 S DIN15401
Overload Limiter	HoistSense® Strain Gauge System

Continued on next page...

Motor power, speed, duty and rating are specified for 460V 60hz feed. Variation in voltage and frequency will change these values.

System Component	Specification
HoistSense® Large Load Display	Present
End Truck Carriage	NXS35 ML Compact Ø150
Hoisting Group	NXS35
Hoisting Motor Power	9.08 kW
Hoisting Control Type	Inverter
Hoisting Brake	CBF06 - 120 Nm
Hoisting Motor Type	4 Pole, Squirrel Cage AC Induction Motor - IP55 - H
Hoisting Gearbox	Hardened, Honed High Precision Helical Gears - 65 HRC
Hoisting Brake	Spring actuated, Electro-magnetic disc
Trolley Motor Power	2.0 $\times$ 0.45 kW
Trolley Drive Gearbox	CF12
Trolley Brake	K2-AS4 - 12 Nm
Trolley Motor Type	4 Pole, Squirrel Cage AC Induction Motor - IP55 - F
Trolley Gearbox Type	Hardened, Honed High Precision Helical Gears - 65 HRC
Trolley Brake Type	Spring actuated, Electro-magnetic disc
Trolley Drive Control	Inverter
Hook Movement Limiter	4 Step Limit (slowdown $\rightarrow$ stop, top & bottom limits)
Electrical Assembly	Fully marked wires, sockets and plugs
Rope Guide	High-performance polymer rope guide
Approximate Weight	900.0 kg
Hoisting Safe Guards	PTC, Thermal Switches, Special Crane Macros
Bearings	SKF / FAG / NACHI / NSK
Hoist Towing Trolley	Present
Color	RAL 5007 - RAL 7046

Continued on next page...

System Component	Specification
End Truck Carriage	
Code	M.3000.W250.20.30.8.3
Wheel Type	250
Wheel Base	3000 mm
Total Length	3504 mm
ETC Connection Type	Top Connection Only
Wheel Quantity	4 Wheels
Construction Classification	A4
Drive Method	Direct Drive
Bearings	SKF / FAG / NACHI / NSK
Long Travel System	
Duty (ISO)	ISO M5 - FEM 2m
Long Travel Drives	2.0 × 0.91 kW CD 22-26.0
Long Travel Control	1.82 kW Inverter
Rail Width	50 mm
Long Travel Speed	6.1 . . . 24.5 m/min
Electrical Assembly	Fully marked wires, sockets and plugs
Cable Festoon System	
System Length	21.0 m
Control Type	Single Hoist Mobile Control (Double Line)
Cable Trolley Type	C Profile
Kit Accessories & Safety Equipment	
Long Travel Limit Switch	4-Level (slowdown/stop - slowdown/stop)
Cross Travel Limit Switch	4-Level (slowdown/stop - slowdown/stop)
Pendant Control	6+1 Pushbutton Pendant with 10.0 m Cable

Continued on next page...

System Component	Specification
Warning Devices	Bridge Warning Siren / Lighting